

PART RPS-300AS		LOT A5X3G	TEST DATA POWER TRANSFORMERS		(有)エレバーツ長野電子パーソン	
SPEC. R320	QUANTITY			DATE Oct. 26, 1995		
		TEMP 20	HUMI %	RH		
Tested 50/60 Hz	Samples.					
Specified	Pri 100 V					
Primary Voltage AC	100V	100				
No-load Pri. Current	mA MAX.	21.8				
Full-load Pri. Current	A.	3.26				
e	0-35V(茶-青) 4 A	Open Voltage Loaded Volt.	37.2 35.1			
o	0-35V(灰-紫) 4 A	Open Voltage Loaded Volt.	37.2 35.1			
t	55/55V(赤-黒-赤) 0.2 A	Open Voltage Loaded Volt.	58.2/58.2 55.2/55.2			
i		Open Voltage Loaded Volt.				
o		Open Voltage Loaded Volt.				
v		Open Voltage Loaded Volt.				
.		Open Voltage Loaded Volt.				
c		Open Voltage Loaded Volt.				
e		Open Voltage Loaded Volt.				
s		Open Voltage Loaded Volt.				
Temp. Rise at Full-load	Resist.M/Thermo.M Max.	- deg(コイル) - deg(コア)				
Dielectric(Core-Wdg.Wdg.-Wdg.)	60 Hz					
Strength	1.5 KV	1 Min	O.K			
Insulation(Core-Wdg.Wdg.-Wdg.)	1 Min.					
Resist D C	500 V	100 M	∞			
		Test Circuit UL1015AWG18 L=400 UL1015 AWG22 L=400 				